

**IN THE SPECIFICATION:**

**Please replace the paragraph beginning at page 3, line 23, with the following rewritten paragraph:**

A hinge structure according to an aspect of the present invention includes: a hinge portion ~~for swingably connecting a pair of connected portions to each other~~ that connects a fixed member and a movable member to each other and allows the movable member to swing relative to the fixed member; and a pair of connection portions adapted to respectively connect the hinge portion to ~~the connected portions~~ the fixed member and the movable member, wherein ~~at least one of the connection portions is extended in an axial direction along a specified surface of one of the connected portions and continuously connected to the specified surface~~ the fixed member has a recessed portion on a surface thereof, and the connection portion on the side of the fixed member is extendedly provided adjacent to the recessed portion.

**Please replace the paragraph beginning at page 4, line 1, with the following rewritten paragraph:**

A hinge structure member according to another aspect of the present invention includes: ~~a pair of connected portions; a hinge portion for swingably connecting the pair of connected portions to each other; and a pair of connection portions adapted to connect the hinge portion to the connected portions, wherein at least one of the connection portions is extended in an axial direction along a~~

~~specified surface of one of the connected portions and continuously connected to the specified surface~~ the aforesaid hinge structure of the present invention.

**Please replace the paragraph beginning at page 13, line 22, with the following rewritten paragraph:**

In contrast, in the present embodiment, the hinge portion ~~[[22]]~~ 21 is bent into substantially U-shape from the middle thereof, so that the tip end of the hinge portion 21 is connected to the upper edge part of the rear surface (a surface 14) of a flange 12 (the other connection portion).

**Please replace the paragraph beginning at page 14, line 5, with the following rewritten paragraph:**

For example, although one support frame 30 is provided with one operation switch 10 in the aforesaid embodiments, there is an alternative configuration in which one support frame 30 is provided with a plurality of operation switches 10 as shown in Fig. ~~[[11]]~~ 12.